



DOORS



Website: keystonedoorspa.com

Email: sales@keystonedoorsolutions.com

Ph: (570) 726-7864

Fax: (570) 726-8024

226 Auction Road, Mill Hall PA 17751



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/0, 2/4, 2/6, 2/8, 2/10, 3/0, 3/6, 4/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2068	25 1/2 × 81 3/4	26 × 82 1/4
2468	29 1/2 × 81 3/4	30 × 82 1/4
2668	31 1/2 × 81 3/4	32 × 82 1/4
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
3668	43 1/2 × 81 3/4	44 × 82 1/4
4068	49 1/2 × 81 3/4	50 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2068	25 1/2 × 80 5/8	26 × 81 1/8
2468	29 1/2 × 80 5/8	30 × 81 1/8
2668	31 1/2 × 80 5/8	32 × 81 1/8
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
3668	43 1/2 × 80 5/8	44 × 81 1/8
4068	49 1/2 × 80 5/8	50 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Fiberglass Door
- "NO ROT" Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White / Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Sill-Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill

AVAILABLE SIZES:

2/6, 2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 81 3/4	32 × 82 1/4
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 80 5/8	32 × 81 1/8
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/6, 2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 81 3/4	32 × 82 1/4
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 80 5/8	32 × 81 1/8
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/6, 2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 81 3/4	32 × 82 1/4
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2668	31 1/2 × 80 5/8	32 × 81 1/8
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 2/10, 3/0, 3/6, 4/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
3668	43 1/2 × 81 3/4	44 × 82 1/4
4068	49 1/2 × 81 3/4	50 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
3668	43 1/2 × 80 5/8	44 × 81 1/8
4068	49 1/2 × 80 5/8	50 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 2/10, 3/0, 3/6, 4/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
3668	43 1/2 × 81 3/4	44 × 82 1/4
4068	49 1/2 × 81 3/4	50 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
3668	43 1/2 × 80 5/8	44 × 81 1/8
4068	49 1/2 × 80 5/8	50 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 2/10, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
21068	35 1/2 × 81 3/4	36 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
21068	35 1/2 × 80 5/8	36 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

3/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill– Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/ Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Smooth Fiberglass Door
- "NO ROT" Smooth Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/
Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded
Adjustable Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Panic Bar & Closure installed

AVAILABLE SIZES:

2/8, 3/0, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 81 3/4	34 × 82 1/4
3068	37 1/2 × 81 3/4	38 × 82 1/4
6068	74 1/2 × 81 3/4	75 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
2868	33 1/2 × 80 5/8	33 × 81 1/8
3068	37 1/2 × 80 5/8	38 × 81 1/8
6068	74 1/2 × 80 5/8	75 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Fiberglass Door
- "NO ROT" Composite Jamb
- Standard Jamb: 4 $\frac{1}{16}$ or 6 $\frac{1}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Sill– Mill Finish
- Inswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Blinds Between Glass
- Double Bore
- Bronze Sill Finish

AVAILABLE SIZES:


12" Sidelight, 14" Sidelight

INSWING DOOR SIZES


	Actual Unit Size	Rough Opening
Double 12" Sidelight	64 1/4 × 81 3/4	81 3/4 × 82 1/4
Double 14" Sidelight	68 1/4 × 81 3/4	68 3/4 × 82 1/4

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Fiberglass Door
- "NO ROT" Composite Jamb
- Standard Jamb: 4 $\frac{9}{16}$ or 6 $\frac{9}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/
Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Sill-
Mill Finish
- Inswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Blinds Between Glass
- Double Bore
- Bronze Sill Finish

AVAILABLE SIZES:


12" Sidelight, 14" Sidelight

INSWING DOOR SIZES


	Actual Unit Size	Rough Opening
Single 12" Sidelight	50 7/8 × 81 3/4	51 3/4 × 82 1/4
Single 14" Sidelight	52 7/8 × 81 3/4	53 3/8 × 82 1/4

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.



KMW SERIES FEATURES

- Insulated Fiberglass Door
- "NO ROT" Composite Jamb
- Standard Jamb: 4 $\frac{9}{16}$ or 6 $\frac{9}{16}$
- Composite Brickmolding
- Door and Jamb are Primed White/Paint Ready
- Single Bore for Latch
- "NO ROT" Injection Molded Sill- Mill Finish
- Inswing or Outswing
- Satin Nickel Ball Bearing Hinges

POPULAR OPTIONS

- Cut Down Height to a Specific Size
- Custom Jamb Width
- Vinyl J Brickmolding
- Paint Door and Jambs
- Blinds Between Glass
- Double Bore
- Bronze Sill Finish
- ADA Sill
- Available in all door styles
- Available in Patio door size: 71 $\frac{3}{4}$ x 79 $\frac{5}{8}$ frame size

AVAILABLE SIZES:

5/4, 5/8, 6/0

INSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
5468	65 7/8 × 81 3/4	66 3/8 × 82 1/4
5868	69 7/8 × 81 3/4	70 3/8 × 82 1/4
6068	73 7/8 × 81 3/4	74 3/4 × 82 1/4

OUTSWING DOOR SIZES


Call Size	Actual Unit Size	Rough Opening
5468	65 7/8 × 80 5/8	66 3/8 × 81 1/8
5868	69 7/8 × 80 5/8	70 3/8 × 81 1/8
6068	73 7/8 × 80 5/8	74 3/8 × 81 1/8

DOOR SWING CHART

Call out the side the knob is on when pulling the door toward you.



Right Hand




Left Hand

INSWING / OUTSWING


View when pulling door towards you.

DOUBLE DOOR SWING CHART

Call out the side the active door is on when pulling the door toward you.



Left Hand Active



Right Hand Active

INSWING / OUTSWING

View when pulling door towards you.